## NSN 5340-01-064-2427

Angle Bracket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-064-2427

| Fabrication Method (non-core):                             |
|--|
| Machined   |
| First Leg Length:  |
| 0.990 inches   |
| Second Leg Length:   |
| Between 2.738 inches and 2.863 inches                      |
| First Leg Hole Diameter:                                   |
| Between 0.276 inches and 0.286 inches                      |
| Second Leg Hole Diameter:                                  |
| 0.221 inches   |
| Second Leg Distance Between Hole Centers Along Length:     |
| 1.725 inches   |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.600 inches   |
| First Leg Thickness:                                       |
| Between 0.056 inches and 0.068 inches                      |
| First Leg Width:   |
| 1.882 inches   |
| First Leg Distance Between Hole Centers Along Width:       |
| 1.382 inches   |
| Second Leg End Radius:                                     |
| Between 0.219 inches and 0.281 inches                      |
| Second Leg Style:  |
| End radius and tapered                                     |
| Second Leg Hole Arrangement Style:                         |
| Two holes  |
| Second Leg Relationship To First Leg:                      |
| Not identical  |
| First Leg Angle:   |
| 90.0 degrees   |
| Material:  |
| Steel  |
| Material Specification:                                    |
| Ams 5512 assn standard single material response            |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
|  |

Fiig:

A042a0