## NSN 5340-01-064-2929

Corner Brace - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-064-2929



### **Material Thickness:** 0.219 mils and 0.281 centimeters Mounting Hole Type: Threaded First Leg Length: Between 7.990 inches and 8.010 inches Second Leg Length: Between 8.844 inches and 8.905 inches Second Leg Width: 0.990 mils and 1.010 centimeters First Leg Hole Diameter: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.719 mils and 0.781 centimeters Second Leg Distance From Edge To Hole Center Along Length: Between 0.990 inches and 1.010 inches Second Leg Slot Length: Between 0.594 inches and 0.656 inches Second Leg Slot Width: Between 0.281 inches and 0.343 inches First Leg Width: Between 0.990 inches and 1.010 inches First Leg Distance Between Hole Centers Along Length: Between 5.990 inches and 6.010 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.719 inches and 0.781 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.469 inches and 0.531 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square Second Leg Hole Arrangement Style: One slot Angle: 90.0 degrees Second Leg Relationship To First Leg: Not identical **Special Features:** For left fender

# NSN 5340-01-064-2929

Corner Brace - Page 2 of 2

Material:

Steel comp 1010

#### Style Designator:

Angle

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A042a0

