

View Online at <https://aerobasegroup.com/nsn/5340-01-066-7755>

**Fabrication Method (non-core):**

Extruded

**First Leg Length:**

4.100 inches

**Second Leg Length:**

4.750 inches

**Second Leg Width:**

1.000 inches

**First Leg Hole Diameter:**

Between 0.266 inches and 0.296 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.830 inches

**Second Leg Slot Length:**

Between 0.330 inches and 0.350 inches

**Second Leg Slot Width:**

Between 0.130 inches and 0.150 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

Between 0.063 inches and 0.083 inches

**First Leg Width:**

1.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.550 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.940 inches

**First Leg Distance Between First And Second Hole Centers Along Length:**

1.160 inches

**First Leg Style:**

Square

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

First leg five holes; fourth and fifth hole 0.550 in. Ctr to ctr; second leg chamfer one end 0.120 in. By 45 degrees

**Material:**

Aluminum alloy 6063

**Material Specification:**

Qq-a-200/8 t6 federal specification single material response or qq-a-200/9 t5 federal specification single material response

**Surface Treatment:**

Anodize

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0