

View Online at <https://aerobasegroup.com/nsn/5340-01-066-7755>

Fabrication Method (non-core):

Extruded

First Leg Length:

4.100 inches

Second Leg Length:

4.750 inches

Second Leg Width:

1.000 inches

First Leg Hole Diameter:

Between 0.266 inches and 0.296 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.830 inches

Second Leg Slot Length:

Between 0.330 inches and 0.350 inches

Second Leg Slot Width:

Between 0.130 inches and 0.150 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

Between 0.063 inches and 0.083 inches

First Leg Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.550 inches

First Leg Distance From Edge To Hole Center Along Length:

0.940 inches

First Leg Distance Between First And Second Hole Centers Along Length:

1.160 inches

First Leg Style:

Square

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg five holes; fourth and fifth hole 0.550 in. Ctr to ctr; second leg chamfer one end 0.120 in. By 45 degrees

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/8 t6 federal specification single material response or qq-a-200/9 t5 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0