

View Online at <https://aerobasegroup.com/nsn/5340-01-067-8918>

Mounting Hole Type:

Plain

First Leg Length:

0.720 inches

Second Leg Length:

0.810 inches

Second Leg Width:

1.000 inches

First Leg Hole Diameter:

Between 0.350 inches and 0.370 inches

Second Leg Hole Diameter:

0.136 inches

Second Leg Distance Between Upper Hole Centers Along Width:

0.500 inches

Second Leg Distance Between Hole Centers Along Length:

0.313 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.187 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

0.525 inches

Center Section Width:

1.000 inches

Center Section Thickness:

0.125 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.370 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.