NSN 5340-01-068-3230

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-068-3230

| First Leg Length: |
|--|
| 0.600 inches |
| Second Leg Length: |
| 0.690 inches |
| Second Leg Width: |
| 0.750 inches |
| First Leg Hole Diameter: |
| 0.166 inches |
| Second Leg Hole Diameter: |
| 0.281 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.380 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.310 inches |
| First Leg Thickness: |
| 0.090 inches |
| Second Leg Thickness: |
| 0.090 inches |
| Center Section Thickness: |
| 0.090 inches |
| First Leg Width: |
| 0.750 inches |
| First Leg Distance Between Hole Centers Along Width: |
| 0.375 inches |
| First Leg Style: |
| Square |
| First Leg Hole Arrangement Style: |
| Two holes |
| Second Leg Style: |
| Square |
| Second Leg Hole Arrangement Style: |
| One hole |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Special Features: |
| Nut mtd on larger dimension leg |
| Material: |
| Aluminum alloy 6061 |
| |

NSN 5340-01-068-3230

Double Angle Bracket - Page 2 of 2



Material Specification:

Qq-a-250/11, alloy 6061, t6 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541, cl a military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.