

View Online at <https://aerobasegroup.com/nsn/5340-01-068-6740>

**Cross Sectional Shape:**

Recess, same shape as the periphery

**Hole Diameter:**

Between 0.217 inches and 0.223 inches

**Width:**

9.313 inches

**Flange Thickness:**

0.040 inches

**Edge Shape:**

Rectangle, four holes

**Length:**

13.938 inches

**Corner Radius:**

0.062 inches

**Distance Between Holes Along Length:**

11.250 inches

**Distance Between Holes Along Width:**

9.000 inches

**Distance From First Hole Centerline To End Along Length:**

1.125 inches

**Distance From First Hole Centerline To End Along Width:**

0.516 inches

**First Recess Inside Height:**

2.750 inches

**Body Thickness:**

0.040 inches

**Securing Device Type:**

Turnlock fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**Special Features:**

Itwo each reinforcement beads molded into top of cover dim typical for both beads l 11.500 in.W 0.938 in.Protusion h 0.250 in.Located from side edge2.000 in.To center of bead-end of beadto edge of cover 1.000 in.Drain hole-dia 0.147 located lower left hand corner in top; upper end side has a rectangular slot opening-molded rolled flange with 0.125 in.Bend radius-protruding 0.188 in.Above end surface-dim of opening-w 3.000 in.-d 2.000 in.Inside corner rad 0.250 in.Located 0.688 in.From right hand side of cover to edge of slot; lower end side has a slot opening-molded rolled flange with 0.125 in.Bend radius-protruding 0.188 in.Above end surface-dim of opening w 1.750 in.Depth 1.875 in.To an inside end radius of slot 0.875 in.Slot located 2.938 in.From right hand side of cover to edge of slot; upper right hand side of cover has a slot opening located 0.438 in.Fromedge of slot to top edge of cover-dim of slot w 1.188 in.D 2.375 in.With inside corner rad 0.250 in.

**Material:**

Plastic

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**