

View Online at <https://aerobasegroup.com/nsn/5340-01-068-6740>

Cross Sectional Shape:

Recess, same shape as the periphery

Hole Diameter:

Between 0.217 inches and 0.223 inches

Width:

9.313 inches

Flange Thickness:

0.040 inches

Edge Shape:

Rectangle, four holes

Length:

13.938 inches

Corner Radius:

0.062 inches

Distance Between Holes Along Length:

11.250 inches

Distance Between Holes Along Width:

9.000 inches

Distance From First Hole Centerline To End Along Length:

1.125 inches

Distance From First Hole Centerline To End Along Width:

0.516 inches

First Recess Inside Height:

2.750 inches

Body Thickness:

0.040 inches

Securing Device Type:

Turnlock fastener

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Itwo each reinforcement beads molded into top of cover dim typical for both beads l 11.500 in.W 0.938 in.Protusion h 0.250 in.Located from side edge2.000 in.To center of bead-end of beadto edge of cover 1.000 in.Drain hole-dia 0.147 located lower left hand corner in top; upper end side has a rectangular slot opening-molded rolled flange with 0.125 in.Bend radius-protruding 0.188 in.Above end surface-dim of opening-w 3.000 in.-d 2.000 in.Inside corner rad 0.250 in.Located 0.688 in.From right hand side of cover to edge of slot; lower end side has a slot opening-molded rolled flange with 0.125 in.Bend radius-protruding 0.188 in.Above end surface-dim of opening w 1.750 in.Depth 1.875 in.To an inside end radius of slot 0.875 in.Slot located 2.938 in.From right hand side of cover to edge of slot; upper right hand side of cover has a slot opening located 0.438 in.Fromedge of slot to top edge of cover-dim of slot w 1.188 in.D 2.375 in.With inside corner rad 0.250 in.

Material:

Plastic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization: