

View Online at <https://aerobasegroup.com/nsn/5340-01-070-1745>

Fabrication Method (non-core):

Cast

Mounting Hole Type:

Countersunk

First Leg Length:

0.880 inches

Second Leg Length:

6.752 inches

Second Leg Width:

4.123 inches

Second Leg Corner Radius:

0.440 inches

First Leg Hole Diameter:

Between 0.271 inches and 0.278 inches

Second Leg Hole Diameter:

Between 0.271 inches and 0.278 inches

Second Leg Distance Between Lower Hole Centers Along Width:

3.243 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.809 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

5.250 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.320 inches

First Leg Style:

Corner radius

Second Leg Style:

Corner radius

First Leg Angle:

90.0 degrees

Special Features:

Left hand usage; heat treatment: mil-h-6088, t-76 cond

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/13, 0 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.