## NSN 5340-01-073-3061

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-073-3061

Cross Sectional Shape: Flat, round rib reinforced Hole Diameter: 0.280 inches Width: 1.880 inches Flange Thickness: 0.372 inches Edge Shape: Rectangle, four holes Length: 1.880 inches Corner Radius: 1.220 inches Distance Between Holes Along Length: 1.320 inches Distance Between Holes Along Width:
Hole Diameter:  0.280 inches  Width:  1.880 inches  Flange Thickness:  0.372 inches  Edge Shape:  Rectangle, four holes  Length:  1.880 inches  Corner Radius:  1.220 inches  Distance Between Holes Along Width:
0.280 inches  Width: 1.880 inches Flange Thickness: 0.372 inches  Edge Shape: Rectangle, four holes  Length: 1.880 inches  Corner Radius: 1.220 inches  Distance Between Holes Along Length: 1.320 inches  Distance Between Holes Along Width:
Width:  1.880 inches  Flange Thickness:  0.372 inches  Edge Shape:  Rectangle, four holes  Length:  1.880 inches  Corner Radius:  1.220 inches  Distance Between Holes Along Length:  1.320 inches  Distance Between Holes Along Width:
1.880 inches  Flange Thickness: 0.372 inches  Edge Shape: Rectangle, four holes  Length: 1.880 inches  Corner Radius: 1.220 inches  Distance Between Holes Along Length: 1.320 inches  Distance Between Holes Along Width:
Flange Thickness:  0.372 inches  Edge Shape: Rectangle, four holes  Length:  1.880 inches  Corner Radius:  1.220 inches  Distance Between Holes Along Length:  1.320 inches  Distance Between Holes Along Width:
0.372 inches  Edge Shape: Rectangle, four holes  Length: 1.880 inches  Corner Radius: 1.220 inches  Distance Between Holes Along Length: 1.320 inches  Distance Between Holes Along Width:
Edge Shape: Rectangle, four holes Length: 1.880 inches Corner Radius: 1.220 inches Distance Between Holes Along Length: 1.320 inches Distance Between Holes Along Width:
Rectangle, four holes  Length:  1.880 inches  Corner Radius:  1.220 inches  Distance Between Holes Along Length:  1.320 inches  Distance Between Holes Along Width:
Length:  1.880 inches  Corner Radius:  1.220 inches  Distance Between Holes Along Length:  1.320 inches  Distance Between Holes Along Width:
1.880 inches  Corner Radius: 1.220 inches  Distance Between Holes Along Length: 1.320 inches  Distance Between Holes Along Width:
Corner Radius:  1.220 inches  Distance Between Holes Along Length:  1.320 inches  Distance Between Holes Along Width:
1.220 inches  Distance Between Holes Along Length: 1.320 inches  Distance Between Holes Along Width:
Distance Between Holes Along Length:  1.320 inches  Distance Between Holes Along Width:
1.320 inches  Distance Between Holes Along Width:
Distance Between Holes Along Width:
1 220 inches
1.320 inches
Distance From First Hole Centerline To End Along Length:
0.280 inches
Distance From First Hole Centerline To End Along Width:
0.280 inches
Body Thickness:
1.220 inches
Securing Device Type:
Special
Mounting Opening Shape Style:
Unthreaded hole
Special Features:
Boss has ring groove 1.063 in. Diameter x 0.188 in. W 0.140 in. From end; boss recess 0.560 in. Diameter x 0.250 deep
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6 al 2024 tp t351 federal specification single material response
Surface Treatment:
Oxide film
Surface Treatment Specification:
Mil-c-5541cl1a military specification single treatment response
Shelf Life:
NV
N/a

## NSN 5340-01-073-3061

Access Cover - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541cl1a spec.