

View Online at <https://aerobasegroup.com/nsn/5340-01-073-9262>

First Leg Length:

Between 0.687 inches and 0.807 inches

Second Leg Length:

Between 0.937 inches and 1.057 inches

Second Leg Width:

Between 0.720 inches and 0.780 inches

Second Leg Corner Radius:

0.219 inches

First Leg Hole Diameter:

Between 0.218 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.135 inches and 0.141 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.365 inches and 0.385 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.150 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 0.720 inches and 0.780 inches

First Leg Corner Radius:

0.219 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.350 inches and 0.410 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 301

Material Specification:

Mil-s-5059 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.