

View Online at <https://aerobasegroup.com/nsn/5340-01-076-6428>

Fabrication Method (non-core):

Stamped

First Leg Length:

2.300 inches

Second Leg Length:

2.000 inches

Reinforcement Method (non-core):

Gusset center section

Second Leg Width:

2.000 inches

First Leg Hole Diameter:

Between 0.268 inches and 0.271 inches

Second Leg Hole Diameter:

Between 0.268 inches and 0.271 inches

Second Leg Distance Between Hole Centers Along Length:

1.625 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.620 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Thickness:

0.120 inches

Second Leg Thickness:

0.120 inches

First Leg Width:

2.300 inches

First Leg Distance Between Hole Centers Along Length:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Distance Between First And Second Hole Centers Along Length:

1.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Surface Treatment:

Oxide film

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0