

View Online at <https://aerobasegroup.com/nsn/5340-01-076-6428>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

2.300 inches

**Second Leg Length:**

2.000 inches

**Reinforcement Method (non-core):**

Gusset center section

**Second Leg Width:**

2.000 inches

**First Leg Hole Diameter:**

Between 0.268 inches and 0.271 inches

**Second Leg Hole Diameter:**

Between 0.268 inches and 0.271 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.625 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.625 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.620 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.620 inches

**First Leg Thickness:**

0.120 inches

**Second Leg Thickness:**

0.120 inches

**First Leg Width:**

2.300 inches

**First Leg Distance Between Hole Centers Along Length:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.620 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Distance Between First And Second Hole Centers Along Length:**

1.500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t4 federal specification single material response

**Surface Treatment:**

Oxide film

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0