

View Online at <https://aerobasegroup.com/nsn/5340-01-077-5895>

Fabrication Method (non-core):

Welded

First Leg Length:

2.500 inches

Second Leg Length:

3.250 inches

Reinforcement Method (non-core):

Gusset both ends

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

Between 0.138 inches and 0.146 inches

Second Leg Hole Diameter:

Between 0.216 inches and 0.224 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance Between Hole Centers Along Length:

2.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.000 inches

First Leg Distance Between Hole Centers Along Width:

1.250 inches

First Leg Distance Between Hole Centers Along Length:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.875 inches

First Leg Distance From Edge To Hole Center Along Length:

0.844 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

1.406 in. Diameter electrical connector mtg hole located in first leg

Material:

Steel comp 304

Surface Treatment:

Passivate

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0