NSN 5340-01-079-5352

Rod End Clevis - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-079-5352

| Thread Class: |
|---|
| 3b rod connection |
| Thread Direction: |
| Right-hand rod connection |
| Thread Length: |
| 0.380 inches rod connection |
| Hole Diameter: |
| Between 0.187 inches and 0.190 inches |
| Shank Diameter: |
| 0.620 inches |
| Overall Height: |
| 0.500 inches |
| Overall Width: |
| 1.060 inches |
| End Radius: |
| 0.280 inches |
| Fork Span Width: |
| Between 0.626 inches and 0.631 inches |
| Securing Pin Hole Diameter: |
| 0.062 inches |
| Distance From Center Of Securing Pin Hole To Rod End: |
| 1.290 inches |
| Distance From Pivot Pinhole Center To Rod Connection End: |
| 1.600 inches |
| Fork Arm Thickness: |
| 0.217 inches |
| Fork Depth: |
| 1.171 inches |
| Thread Size: |
| 0.312 inches rod connection |
| Special Features: |
| Shank countersunk 90 degrees by 0.310 in. Dia, four slots spaced 90 degrees apart |
| Material: |
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Dps 9.74, type 2, cage 88277 mfr ref single treatment response |

Unf rod connection

Thread Series Designator:

NSN 5340-01-079-5352

Rod End Clevis - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A264a0 | |

Shelf Life:

Mil-std (military Standard): Mil-s-6758 spec.