

View Online at <https://aerobasegroup.com/nsn/5340-01-080-2252>

**First Leg Length:**

Between 0.800 inches and 0.840 inches

**Second Leg Length:**

Between 1.450 inches and 1.490 inches

**Second Leg Width:**

Between 0.485 inches and 0.515 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.210 inches and 0.230 inches

**First Leg Thickness:**

Between 0.056 inches and 0.069 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.069 inches

**First Leg Width:**

Between 0.485 inches and 0.515 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.210 inches and 0.230 inches

**First Leg End Radius:**

Between 0.344 inches and 0.406 inches

**Second Leg End Radius:**

Between 0.344 inches and 0.406 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 630 or steel

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiiq:**

A042a0