## NSN 5340-01-080-8910

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-080-8910

Fabrication Method (non-core):
Welded
Mounting Hole Type:
Plain
First Leg Length:
2.495 inches
Second Leg Length:
6.025 inches
End Application:
2350-00-873-5408
Second Leg Width:
1.640 inches
First Leg Hole Diameter:
0.560 inches
Second Leg Hole Diameter:
0.680 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.820 inches
First Leg Thickness:
0.375 inches
Second Leg Thickness:
0.375 inches
Center Section Height:
11.320 inches
Center Section Width:
4.260 inches
Center Section Thickness:
0.375 inches
First Leg Width:
4.260 inches
First Leg Distance Between Hole Centers Along Width:
3.250 inches
First Leg Distance From Edge To Hole Center Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.500 inches
Second Leg End Radius:
0.820 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:

Two holes

## NSN 5340-01-080-8910

Double Angle Bracket - Page 2 of 2



Second Leg Style:
End radius
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Aluminum alloy 6061 or aluminum alloy 5052
Material Specification:
Qq-a-250/11, temper 0 federal specification single material response or qq-a-250/8, temper 0 federal specification single material response
Surface Treatment:
Chromate and enamel
Surface Treatment Specification:
Mil-c-5541, class 1a military specification 1st treatment response and tt-e-485 federal specification 2nd treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.