

View Online at <https://aerobasegroup.com/nsn/5340-01-082-7948>

**Mounting Hole Type:**

Counterbored and threaded

**First Leg Length:**

1.980 inches

**Second Leg Length:**

0.900 inches

**Second Leg Width:**

Between 3.420 inches and 3.460 inches

**Second Leg End Width:**

Between 0.600 inches and 0.640 inches

**First Leg Slot Length:**

Between 0.650 inches and 0.660 inches

**First Leg Slot Width:**

0.190 inches

**Second Leg Hole Diameter:**

Between 0.270 inches and 0.284 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.570 inches

**First Leg Thickness:**

Between 0.120 inches and 0.130 inches

**Second Leg Thickness:**

Between 0.120 inches and 0.130 inches

**First Leg Width:**

3.087 inches

**First Leg Distance Between Hole Centers Along Width:**

2.734 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.353 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.520 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Offset Angle:**

15.0 degrees

**Special Features:**

Hole on first leg 0.050 to 0.060 in. Through and one small hole 0.190 in. Diameter to 0.210 in. Dia, countersink 80 degrees to 120 degrees, threaded 190-32 unf 3b; second leg fourth hole 0.270 in. Diameter to 0.284 in. Dia

**Material:**

Stainless steel

**Material Specification:**

Ams 5599 assn standard single material response or ams 5666 assn standard single material response

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0