

View Online at <https://aerobasegroup.com/nsn/5340-01-082-7948>

Mounting Hole Type:

Counterbored and threaded

First Leg Length:

1.980 inches

Second Leg Length:

0.900 inches

Second Leg Width:

Between 3.420 inches and 3.460 inches

Second Leg End Width:

Between 0.600 inches and 0.640 inches

First Leg Slot Length:

Between 0.650 inches and 0.660 inches

First Leg Slot Width:

0.190 inches

Second Leg Hole Diameter:

Between 0.270 inches and 0.284 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.570 inches

First Leg Thickness:

Between 0.120 inches and 0.130 inches

Second Leg Thickness:

Between 0.120 inches and 0.130 inches

First Leg Width:

3.087 inches

First Leg Distance Between Hole Centers Along Width:

2.734 inches

First Leg Distance From Edge To Hole Center Along Width:

0.353 inches

First Leg Distance From Edge To Hole Center Along Length:

0.520 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Offset Angle:

15.0 degrees

Special Features:

Hole on first leg 0.050 to 0.060 in. Through and one small hole 0.190 in. Diameter to 0.210 in. Dia, countersink 80 degrees to 120 degrees, threaded 190-32 unf 3b; second leg fourth hole 0.270 in. Diameter to 0.284 in. Dia

Material:

Stainless steel

Material Specification:

Ams 5599 assn standard single material response or ams 5666 assn standard single material response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0