

View Online at <https://aerobasegroup.com/nsn/5340-01-083-9624>

**Fabrication Method (non-core):**

Any acceptable

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.000 inches

**Second Leg Length:**

2.750 inches

**Second Leg Width:**

1.910 inches

**Second Leg End Width:**

0.800 inches

**First Leg Hole Diameter:**

Between 0.234 inches and 0.240 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**Second Leg Slot Length:**

0.360 inches

**Second Leg Slot Width:**

0.260 inches

**First Leg Thickness:**

Between 0.076 inches and 0.084 inches

**Second Leg Thickness:**

Between 0.076 inches and 0.084 inches

**First Leg Width:**

1.910 inches

**First Leg Corner Radius:**

0.310 inches

**First Leg Distance Between Hole Centers Along Width:**

1.160 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.216 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Left hand mtg

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/4, t0 federal specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0