

View Online at <https://aerobasegroup.com/nsn/5340-01-083-9625>

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

First Leg Length:

1.000 inches

Second Leg Length:

2.750 inches

Second Leg Width:

1.910 inches

Second Leg End Width:

0.800 inches

First Leg Hole Diameter:

Between 0.234 inches and 0.240 inches

Second Leg Distance Between Hole Centers Along Length:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

Second Leg Slot Length:

0.360 inches

Second Leg Slot Width:

0.260 inches

First Leg Thickness:

Between 0.076 inches and 0.084 inches

Second Leg Thickness:

Between 0.076 inches and 0.084 inches

First Leg Width:

1.910 inches

First Leg Corner Radius:

0.310 inches

First Leg Distance Between Hole Centers Along Width:

1.160 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.253 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Rh mounting

Material:

Aluminum alloy 2024

Surface Treatment Specification:

Qq-a-250/4, tc federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0