NSN 5340-01-084-2663

Swivel Caster - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-01-084-2663 |
|---|
| Center To Center Distance Between Bolt Holes Along Width: |
| 3.125 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 4.625 inches |
| Wheel Quantity: |
| 1 |
| Tire Size: |
| 4.10/3.50-6 |
| Safe Operating Load Rating: |
| 295.0 pounds |
| Material And Location: |
| Steel wheel rim err-100 err-100 |
| Unpackaged Unit Weight: |
| 49.000 pounds |
| Wheel Type: |
| Pneumatic tire |
| Wheel Diameter: |
| 12.800 inches |
| Effective Height: |
| 16.500 inches |
| Plate Style: |
| Rectangular |
| Wheel Bearing Type: |
| Ball |
| Swivel Bearing Type: |
| Ball |
| Swivel Bearing Arrangement: |
| Two row |
| King Bolt Bearing Type: |
| Ball |
| Tread Width: |
| 4.000 inches |
| Caster Plate Length: |
| 6.000 inches |
| Caster Plate Width: |
| 4.500 inches |
| Caster Plate Mounting Hole Diameter: |
| 0.500 inches |
| Special Features: |

N/a

Shelf Life:

Coil spring suspension included

NSN 5340-01-084-2663

Swivel Caster - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A25600