

View Online at <https://aerobasegroup.com/nsn/5340-01-084-4028>

Fabrication Method (non-core):

Welded

Mounting Hole Type:

Plain

First Leg Length:

2.940 inches

Second Leg Length:

3.190 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

1.500 inches

First Leg Slot Length:

0.500 inches

First Leg Slot Width:

Between 0.214 inches and 0.224 inches

Second Leg Distance Between Hole Centers Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.840 inches

Second Leg Slot Length:

1.320 inches

Second Leg Slot Width:

Between 0.214 inches and 0.224 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.500 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.390 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.