

View Online at <https://aerobasegroup.com/nsn/5340-01-084-4028>

**Fabrication Method (non-core):**

Welded

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.940 inches

**Second Leg Length:**

3.190 inches

**Reinforcement Method (non-core):**

Gusset both legs

**Second Leg Width:**

1.500 inches

**First Leg Slot Length:**

0.500 inches

**First Leg Slot Width:**

Between 0.214 inches and 0.224 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.840 inches

**Second Leg Slot Length:**

1.320 inches

**Second Leg Slot Width:**

Between 0.214 inches and 0.224 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

1.500 inches

**First Leg Distance Between Hole Centers Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.390 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.