

View Online at <https://aerobasegroup.com/nsn/5340-01-086-8613>

First Leg Length:

1.125 inches

Second Leg Length:

1.188 inches

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.438 inches

Second Leg Slot Length:

0.500 inches

Second Leg Slot Width:

0.250 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

Center Section Height:

0.625 inches

Center Section Width:

0.750 inches

Center Section Thickness:

0.050 inches

First Leg Width:

0.750 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.375 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.188 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg Distance Between First And Second Hole Centers Along Length:

0.188 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

0.188 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Color gold

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, t0 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.