

View Online at <https://aerobasegroup.com/nsn/5340-01-088-0328>

Mounting Hole Type:

Plain

First Leg Length:

0.500 inches

Second Leg Length:

0.620 inches

Second Leg Width:

1.200 inches

First Leg Slot Length:

0.250 inches

First Leg Slot Width:

0.125 inches

Second Leg Distance Between Hole Centers Along Width:

0.800 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.200 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg Slot Length:

0.250 inches

Second Leg Slot Width:

0.125 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

Center Section Height:

Between 0.600 inches and 0.620 inches

Center Section Width:

1.200 inches

Center Section Thickness:

0.040 inches

First Leg Width:

1.200 inches

First Leg End Width:

0.700 inches

First Leg Distance Between Hole Centers Along Width:

0.400 inches

First Leg Distance From Edge To Hole Center Along Width:

0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Color light gray

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Ps83603ge, fscm 97942 mfr ref single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0