

View Online at <https://aerobasegroup.com/nsn/5340-01-091-2051>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.752 inches and 0.784 inches

Second Leg Length:

Between 1.270 inches and 1.290 inches

Second Leg Width:

Between 0.950 inches and 0.970 inches

Second Leg Corner Radius:

Between 0.094 inches and 0.125 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.480 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.264 inches and 0.284 inches

First Leg Thickness:

Between 0.098 inches and 0.112 inches

Second Leg Thickness:

Between 0.098 inches and 0.112 inches

First Leg Width:

1.156 inches

First Leg Distance Between Hole Centers Along Width:

0.624 inches

First Leg Distance From Edge To Hole Center Along Width:

0.110 inches

First Leg Distance From Edge To Hole Center Along Length:

0.110 inches

First Leg End Radius:

Between 0.234 inches and 0.266 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4911 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0