

View Online at <https://aerobasegroup.com/nsn/5340-01-091-3954>

**Fabrication Method (non-core):**

Cast

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

0.880 inches

**Second Leg Length:**

6.752 inches

**Second Leg Width:**

4.123 inches

**Second Leg Corner Radius:**

0.440 inches

**First Leg Hole Diameter:**

Between 0.271 inches and 0.278 inches

**Second Leg Hole Diameter:**

Between 0.271 inches and 0.278 inches

**Second Leg Distance Between Lower Hole Centers Along Width:**

3.243 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.809 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

5.250 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.320 inches

**First Leg Style:**

Corner radius

**Second Leg Style:**

Corner radius

**First Leg Angle:**

90.0 degrees

**Special Features:**

Right hand usage; heat treatment: mil-h-6088, t-76 cond

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-250/13, 0 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.