

View Online at <https://aerobasegroup.com/nsn/5340-01-093-5215>

**First Leg Length:**

Between 0.590 inches and 0.650 inches

**Second Leg Length:**

Between 1.295 inches and 1.315 inches

**Second Leg Width:**

Between 0.470 inches and 0.530 inches

**First Leg Hole Diameter:**

0.204 inches

**Second Leg Hole Diameter:**

0.401 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.365 inches and 0.385 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.365 inches and 0.385 inches

**First Leg Thickness:**

Between 0.070 inches and 0.090 inches

**Second Leg Thickness:**

Between 0.070 inches and 0.090 inches

**First Leg Width:**

Between 0.470 inches and 0.530 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.160 inches and 0.220 inches

**First Leg End Radius:**

Between 0.160 inches and 0.220 inches

**Second Leg End Radius:**

Between 0.365 inches and 0.385 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-18729, cond n military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-18729 spec.