## NSN 5340-01-093-5241

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-093-5241

Cross Sectional Shape:
Square or rectangular recess
Hole Diameter:
Between 0.323 inches and 0.333 inches
Width:
5.060 inches
Flange Thickness:
0.060 inches
Edge Shape:
Rectangle, four holes
Length:
6.680 inches
Inside Width:
4.940 inches
Inside Length:
6.560 inches
Distance Between Holes Along Length:
5.750 inches
Distance Between Holes Along Width:
4.125 inches
Distance From First Hole Centerline To End Along Length:
0.465 inches
0.465 inches  Distance From First Hole Centerline To End Along Width:
Distance From First Hole Centerline To End Along Width:
Distance From First Hole Centerline To End Along Width: 0.468 inches
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:
Distance From First Hole Centerline To End Along Width: 0.468 inches First Recess Inside Height: 0.370 inches
Distance From First Hole Centerline To End Along Width: 0.468 inches First Recess Inside Height: 0.370 inches Inside Corner Radius:
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches
Distance From First Hole Centerline To End Along Width: 0.468 inches First Recess Inside Height: 0.370 inches Inside Corner Radius: 0.060 inches Body Thickness:
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:  Threaded fastener
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:  Threaded fastener  Mounting Opening Shape Style:
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:  Threaded fastener  Mounting Opening Shape Style:  Unthreaded hole
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:  Threaded fastener  Mounting Opening Shape Style:  Unthreaded hole  Special Features:
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:  Threaded fastener  Mounting Opening Shape Style:  Unthreaded hole  Special Features:  Color, forest green
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:  Threaded fastener  Mounting Opening Shape Style:  Unthreaded hole  Special Features:  Color, forest green  Material:
Distance From First Hole Centerline To End Along Width:  0.468 inches  First Recess Inside Height:  0.370 inches  Inside Corner Radius:  0.060 inches  Body Thickness:  0.060 inches  Securing Device Type:  Threaded fastener  Mounting Opening Shape Style:  Unthreaded hole  Special Features:  Color, forest green  Material:  Steel

Enamel

## NSN 5340-01-093-5241

Access Cover - Page 2 of 2



## **Surface Treatment Specification:**

Mil-e-52798 military sp	ecification single treatme	ent response or mil-e-5	2835 military specificatio	n single treatment response
-------------------------	----------------------------	-------------------------	----------------------------	-----------------------------

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-e-52798 spec.