

View Online at <https://aerobasegroup.com/nsn/5340-01-093-9519>

Cross Sectional Shape:

Square or rectangular recess

Hole Diameter:

Between 0.114 inches and 0.120 inches

Width:

Between 2.760 inches and 2.780 inches

Flange Thickness:

Between 0.037 inches and 0.043 inches

Edge Shape:

Rectangle, multi holes

Length:

Between 5.740 inches and 5.760 inches

Inside Width:

Between 2.690 inches and 2.710 inches

Inside Length:

5.680 inches

Corner Radius:

0.120 inches

Hole Quantity Along Length:

2

Hole Quantity Along Width:

2

Distance Between Holes Along Length:

0.450 inches

Distance Between Holes Along Width:

2.420 inches

Distance From First Hole Centerline To End Along Length:

Between 0.170 inches and 0.190 inches

Distance From First Hole Centerline To End Along Width:

Between 0.170 inches and 0.190 inches

First Recess Inside Height:

Between 0.262 inches and 0.268 inches

Inside Corner Radius:

0.060 inches

Body Thickness:

Between 0.262 inches and 0.268 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, o federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Fsc Application Data:

Data transfer module

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.