

View Online at <https://aerobasegroup.com/nsn/5340-01-094-1426>

First Leg Length:

0.750 inches

Second Leg Length:

0.790 inches

First Leg Hole Diameter:

0.185 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.820 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.312 inches

Second Leg Slot Length:

0.312 inches

Second Leg Slot Width:

0.250 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

3.180 inches

First Leg Distance Between Hole Centers Along Width:

2.780 inches

First Leg Distance From Edge To Hole Center Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Length:

0.234 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Enamel and oxide film

Surface Treatment Specification:

Fed standard 595 federal standard 1st treatment response and mil-c-5541, type 1, cl 3 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.