

View Online at <https://aerobasegroup.com/nsn/5340-01-094-1427>

**First Leg Length:**

0.790 inches

**Second Leg Length:**

0.850 inches

**Second Leg Width:**

3.180 inches

**First Leg Slot Length:**

0.312 inches

**First Leg Slot Width:**

0.250 inches

**Second Leg Hole Diameter:**

0.185 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.780 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.190 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.390 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.360 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Heat Treatment:**

H-32 strain hardened

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, h32 federal specification single material response

**Surface Treatment:**

Enamel and oxide film

**Surface Treatment Specification:**

Fed standard 595 federal standard 1st treatment response and mil-c-5541, type 1, cl 3 military specification 2nd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.