

View Online at <https://aerobasegroup.com/nsn/5340-01-095-3228>

Fabrication Method (non-core):

Machined

First Leg Length:

0.210 inches

Second Leg Length:

0.240 inches

Second Leg Width:

0.250 inches

Second Leg Hole Diameter:

0.129 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.120 inches

First Leg Thickness:

0.020 inches

Second Leg Thickness:

0.020 inches

Center Section Height:

0.450 inches

Center Section Width:

Between 0.125 inches and 0.130 inches

Center Section Thickness:

0.020 inches

First Leg Width:

0.120 inches

First Leg End Radius:

Between 0.060 inches and 0.090 inches

Second Leg End Radius:

Between 0.120 inches and 0.150 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 301

Material Specification:

Mil-s-5059, t 301 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.