

View Online at <https://aerobasegroup.com/nsn/5340-01-096-9106>

First Leg Length:

Between 0.720 inches and 0.780 inches

Second Leg Length:

Between 0.720 inches and 0.780 inches

Second Leg Width:

Between 1.510 inches and 1.570 inches

First Leg Hole Diameter:

0.191 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Width:

0.880 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.330 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.330 inches

First Leg Thickness:

Between 0.053 inches and 0.073 inches

Second Leg Thickness:

Between 0.053 inches and 0.073 inches

First Leg Width:

Between 1.510 inches and 1.570 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.740 inches and 0.800 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.360 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t3 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.