

View Online at <https://aerobasegroup.com/nsn/5340-01-097-9997>

**First Leg Length:**

Between 0.890 inches and 0.950 inches

**Second Leg Length:**

Between 0.890 inches and 0.950 inches

**Second Leg Width:**

Between 1.470 inches and 1.530 inches

**First Leg Hole Diameter:**

0.203 inches

**Second Leg Hole Diameter:**

0.203 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.740 inches and 0.760 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.350 inches and 0.410 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.350 inches and 0.410 inches

**First Leg Thickness:**

Between 0.061 inches and 0.071 inches

**Second Leg Thickness:**

Between 0.061 inches and 0.071 inches

**First Leg Width:**

Between 1.470 inches and 1.530 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.740 inches and 0.760 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.350 inches and 0.410 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.350 inches and 0.410 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-18729 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl2 federal specification all treatment responses

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-18729 spec.