

View Online at <https://aerobasegroup.com/nsn/5340-01-097-9997>

First Leg Length:

Between 0.890 inches and 0.950 inches

Second Leg Length:

Between 0.890 inches and 0.950 inches

Second Leg Width:

Between 1.470 inches and 1.530 inches

First Leg Hole Diameter:

0.203 inches

Second Leg Hole Diameter:

0.203 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.740 inches and 0.760 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.350 inches and 0.410 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

First Leg Thickness:

Between 0.061 inches and 0.071 inches

Second Leg Thickness:

Between 0.061 inches and 0.071 inches

First Leg Width:

Between 1.470 inches and 1.530 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.740 inches and 0.760 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.350 inches and 0.410 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Material:

Steel comp 4130

Material Specification:

Mil-s-18729 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.