

View Online at <https://aerobasegroup.com/nsn/5340-01-098-0733>

First Leg Length:

Between 0.990 inches and 1.010 inches

Second Leg Length:

Between 0.990 inches and 1.010 inches

Second Leg Width:

Between 1.530 inches and 1.590 inches

First Leg Hole Diameter:

0.271 inches

Second Leg Hole Diameter:

0.221 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.802 inches and 0.822 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.350 inches and 0.410 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

First Leg Thickness:

Between 0.052 inches and 0.072 inches

Second Leg Thickness:

Between 0.052 inches and 0.072 inches

First Leg Width:

Between 0.720 inches and 0.780 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.350 inches and 0.410 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

45.0 degrees

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-200/11, t6511 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.