

View Online at <https://aerobasegroup.com/nsn/5340-01-098-0733>

**First Leg Length:**

Between 0.990 inches and 1.010 inches

**Second Leg Length:**

Between 0.990 inches and 1.010 inches

**Second Leg Width:**

Between 1.530 inches and 1.590 inches

**First Leg Hole Diameter:**

0.271 inches

**Second Leg Hole Diameter:**

0.221 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.802 inches and 0.822 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.350 inches and 0.410 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.350 inches and 0.410 inches

**First Leg Thickness:**

Between 0.052 inches and 0.072 inches

**Second Leg Thickness:**

Between 0.052 inches and 0.072 inches

**First Leg Width:**

Between 0.720 inches and 0.780 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.350 inches and 0.410 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.350 inches and 0.410 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

45.0 degrees

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-200/11, t6511 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.