

View Online at <https://aerobasegroup.com/nsn/5340-01-098-2227>

Mounting Hole Type:

Plain and threaded

First Leg Length:

3.240 inches

Second Leg Length:

3.380 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

8.500 inches

Second Leg Corner Radius:

0.500 inches

First Leg Hole Diameter:

0.420 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

0.750 inches

Second Leg Distance Between Hole Centers Along Length:

7.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.120 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.120 inches

Second Leg Thickness:

0.120 inches

Center Section Width:

8.500 inches

Center Section Thickness:

0.120 inches

First Leg Width:

2.780 inches

First Leg End Width:

2.000 inches

First Leg Distance Between Hole Centers Along Width:

1.290 inches

First Leg Distance Between Hole Centers Along Length:

4.833 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

Second Leg Angle:

90.0 degrees

First Leg Offset Angle:

16.0 degrees

Special Features:

Center section wedge-shape 0.062 to 3.000 high; first leg holes are on strap 10884373 w/nuts ms27128-5

Material:

Steel

Material Specification:

Qq-s-698 qa commercial federal specification single material response

Style Designator:

Offset double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0