

View Online at <https://aerobasegroup.com/nsn/5340-01-099-0792>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.556 inches

Second Leg Length:

0.425 inches

Furnished Items (non-core):

Clinch nut

Second Leg Width:

0.450 inches

First Leg Hole Diameter:

0.128 inches

Second Leg Hole Diameter:

Between 0.217 inches and 0.219 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.225 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.225 inches

First Leg Thickness:

Between 0.046 inches and 0.054 inches

Second Leg Thickness:

Between 0.046 inches and 0.054 inches

First Leg Width:

1.250 inches

First Leg Distance Between Hole Centers Along Width:

0.874 inches

First Leg Distance From Edge To Hole Center Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Length:

0.155 inches

Second Leg End Radius:

0.225 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Items furnished as accessories: clinch nut

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541, type 2, grade c, class 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.