NSN 5340-01-099-4158

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-099-4158 First Leg Length: 0.425 inches Second Leg Length: 0.556 inches Second Leg Width: 0.450 inches First Leg Hole Diameter: 0.128 inches Second Leg Hole Diameter: Between 0.217 inches and 0.219 inches Second Leg Distance From Edge To Hole Center Along Width: 0.225 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.225 inches First Leg Thickness: Between 0.046 inches and 0.054 inches Second Leg Thickness: Between 0.046 inches and 0.054 inches First Leg Width: 1.250 inches First Leg Distance Between Hole Centers Along Width: 0.874 inches First Leg Distance From Edge To Hole Center Along Width: 0.188 inches First Leg Distance From Edge To Hole Center Along Length: 0.155 inches Second Leg End Radius: 0.225 inches First Leg Style: Extended flat First Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg:

Second Leg Style: End radius Second Leg Hole Arrangement Style: One hole Not identical First Leg Angle: 90.0 degrees Material: Aluminum alloy 5052

NSN 5340-01-099-4158

Angle Bracket - Page 2 of 2

Mil-std (military Standard):

Mil-c-5541 spec.



| Material Specification: |
|--|
| Qq-a-250/8, h32 federal specification single material response |
| Surface Treatment: |
| Oxide film |
| Surface Treatment Specification: |
| $\label{eq:mil-c-5541} \mbox{Mil-c-5541, type 2, grade 3, class 3 military specification single treatment response}$ |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |