

View Online at <https://aerobasegroup.com/nsn/5340-01-101-9868>

First Leg Length:

Between 1.480 inches and 1.540 inches

Second Leg Length:

Between 1.610 inches and 1.670 inches

Second Leg Width:

Between 0.590 inches and 0.650 inches

Second Leg Corner Radius:

0.430 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Length:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

Between 0.040 inches and 0.060 inches

Second Leg Thickness:

Between 0.040 inches and 0.060 inches

First Leg Width:

Between 0.590 inches and 0.650 inches

First Leg Corner Radius:

0.430 inches

First Leg Distance Between Hole Centers Along Length:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

93.0 degrees

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/13, t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.