

View Online at <https://aerobasegroup.com/nsn/5340-01-102-7412>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

0.910 inches

Second Leg Width:

1.310 inches

Second Leg Corner Radius:

0.310 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

0.094 in. Diameter lockwire hole in second leg

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, t81 federal specification single material response

Surface Treatment:

Chromate and primer

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.