

View Online at <https://aerobasegroup.com/nsn/5340-01-103-8759>

First Leg Length:

2.600 inches

Second Leg Length:

11.260 inches

Second Leg Width:

7.000 inches

Second Leg Corner Radius:

0.500 inches

First Leg Hole Diameter:

0.343 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Lower Hole Centers Along Width:

4.940 inches

Second Leg Distance Between Hole Centers Along Length:

4.360 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

4.940 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.600 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.860 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

7.000 inches

First Leg Corner Radius:

0.500 inches

First Leg Distance Between Hole Centers Along Width:

6.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.510 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Enameled olive drab

Material:

Steel comp 1010 or steel comp 1020

Material Specification:

Qq-s-693 federal specification single material response

Surface Treatment:

Phosphate zinc and primer

Surface Treatment Specification:

Tt-c-490 federal specification 1st treatment response and ttp-636 federal specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0