

View Online at <https://aerobasegroup.com/nsn/5340-01-104-4959>

**Fabrication Method (non-core):**

Any acceptable

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.750 inches

**Second Leg Length:**

0.800 inches

**Second Leg Width:**

1.300 inches

**Second Leg Corner Radius:**

0.300 inches

**First Leg Hole Diameter:**

Between 0.129 inches and 0.134 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.550 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.300 inches

**Second Leg Slot Length:**

0.505 inches

**Second Leg Slot Width:**

Between 0.224 inches and 0.234 inches

**First Leg Thickness:**

0.071 inches

**Second Leg Thickness:**

0.071 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Right hand and inverted clip nut installation

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, t72 or t61 federal specification single material response

**Surface Treatment:**

Chromate and primer

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.