## NSN 5340-01-104-4960

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-104-4960

**Fabrication Method (non-core):** 

Any acceptable

First Leg Length:

0.750 inches

Second Leg Length:

0.750 inches

Second Leg Width:

Between 0.980 inches and 1.020 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.230 inches

Second Leg Distance Between Hole Centers Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

Between 0.980 inches and 1.020 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

## NSN 5340-01-104-4960

Angle Bracket - Page 2 of 2

Mil-p-23377 spec.



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/5, t81 federal specification single material response
Surface Treatment:
Paint
Surface Treatment Specification:
Mil-p-23377 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):