

View Online at <https://aerobasegroup.com/nsn/5340-01-104-4960>

**Fabrication Method (non-core):**

Any acceptable

**First Leg Length:**

0.750 inches

**Second Leg Length:**

0.750 inches

**Second Leg Width:**

Between 0.980 inches and 1.020 inches

**Second Leg Corner Radius:**

Between 0.220 inches and 0.280 inches

**First Leg Hole Diameter:**

Between 0.129 inches and 0.134 inches

**Second Leg Hole Diameter:**

Between 0.220 inches and 0.230 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.220 inches and 0.280 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**First Leg Width:**

Between 0.980 inches and 1.020 inches

**First Leg Corner Radius:**

Between 0.220 inches and 0.280 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.220 inches and 0.280 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, t81 federal specification single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-p-23377 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.