

View Online at <https://aerobasegroup.com/nsn/5340-01-104-4960>

Fabrication Method (non-core):

Any acceptable

First Leg Length:

0.750 inches

Second Leg Length:

0.750 inches

Second Leg Width:

Between 0.980 inches and 1.020 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.230 inches

Second Leg Distance Between Hole Centers Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

Between 0.980 inches and 1.020 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, t81 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-p-23377 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-p-23377 spec.