## NSN 5340-01-105-8922

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-105-8922 First Leg Length: 0.430 inches Second Leg Length: 0.700 inches Second Leg End Width: 0.270 inches First Leg Hole Diameter: 0.166 inches **Second Leg Hole Diameter:** 0.188 inches Second Leg Distance From Edge To Hole Center Along Width: 0.740 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.260 inches First Leg Thickness: 0.090 inches **Second Leg Thickness:** 0.090 inches **Center Section Height:** 0.930 inches **Center Section Width:** 1.320 inches **Center Section Thickness:** 0.090 inches First Leg Width: 1.320 inches First Leg Distance Between Hole Centers Along Width: 0.956 inches First Leg Distance From Edge To Hole Center Along Width: 0.122 inches First Leg Distance From Edge To Hole Center Along Length: 0.120 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Angle **Second Leg Hole Arrangement Style:** 

Second Leg Relationship To First Leg: Not identical

## NSN 5340-01-105-8922

Double Angle Bracket - Page 2 of 2



| First Leg Angle:  |
|---|
| 90.0 degrees  |
| Second Leg Angle:   |
| 90.0 degrees  |
| Material:   |
| Aluminum alloy 6061   |
| Surface Treatment:  |
| Oxide film  |
| Surface Treatment Specification:                                  |
| Mil-c-5541, cl 3 military specification single treatment response |
| Style Designator:   |
| Double angle  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A042a0  |
| Mil-std (military Standard):                                      |
| Mil-c-5541 spec.  |